

X53

For big applications
Pentru operatiuni complexe



In stainless steel.
Din otel inoxidabil



A hot wash degreasing machine for heavy duty components using no hazardous detergents in a single stage wash cycle



Masina de spalat si degresat cu apa calda piese mari si grele cu detergenti pe baza de apa in o singura etapa de spalare

WATER BASED
AD ACQUA
AVEC EAU
CON AGUA
MIT WASSER


X53
SPECIFICATIONS - DATE TEHNICE

		L160	L190	L210	L240
Basket / Cos	mm	1100x1100	1300x1300	1500x1500	1800x1800
Load height / Greutate incarcatura	mm	800	900	1000	1000
Cleaning temperature / Temperatura curatare	°C	75	75	75	75
Load weight/ Greutate incarcatura	kg	700	700	700	700
Tank capacity / Capacitate rezervor	l	300	400	500	700
Water heater (With burner) / Incalzire apa	kcal/h	29000	29000	29000	29000
Tank heating element / Element de incalzire a rezervorului	kW	20	30	30	36
Wash pump: Pompa spalare					
■ Spray rate ■ Rata pulverizare	l/min	450	500	550	550
■ Spray pressure ■ Presiune pulverizare	bar	4	4,5	4,5	4,5
■ Pump ■ Pompa	hp	7,5	10	10	10
Motorised basket rotation: Rotatia motorizata a cosului					
■ Power rating ■ Putere	hp	0,5	0,5	0,5	0,5
■ Speed of basket ■ Viteza de rotire a cosului	rpm	7	7	7	7
Electro / extractor fan: Ventilator extractie aburi din incinta					
■ Outlet ■ Capacitate	m³/h	800	800	800	800
■ Power rating ■ Putere	hp	0,75	0,75	0,75	0,75
Power requirements (With burner) / Cerinte alimentare (cu arzator)	kW	7	7	9	9
Power requirements (Electrical) / Cerinte alimentare (electric)	kW	27	37	39	39
Insulation / Izolatie	-	Standard	Standard	Standard	Standard
Voltage / Voltaj	V	400 V	400 V	400 V	400 V
Phases / Faze	Ph	3+N	3+N	3+N	3+N
Door open / Usa deschisa	mm	2100x2950x2950	2300x3300x3150	2500x3750x3350	2800x4330x3350


We reserve the right to modify without notice - Ne rezervam dreptul de a face modificari in brosură fara a anunta in prealabil

OPTIONAL


- Fresh water rinse
- Clătire cu apă curată



- Hot drying
- Uscare la cald



- Oil skimmer
- Skimmer ulei



- Load weight 1500 kg
- Greutate incarcatura 1500 KG