

## X51 Series Spray Cabinet Washers

Low water level shut-off included  
Oprire automata cand nivelul  
apei este scazut



L101

1 Pump / Pompa



L102




L122



L152

2 Pumps / Pompe



In stainless steel  
Din otel inoxidabil



Automatic parts washers with hot water  
and biodegradable detergent for medium applications




Masini pentru spalat piese cu apa calda si detergent  
pe baza de apa




**X51 Series Spray Cabinet Washers**
**SPECIFICATIONS - DATE TEHNICE**

		<b>L101</b>	<b>L102</b>	<b>L122</b>	<b>L152</b>
Basket diam. / Diametrul cosului	mm	910	910	1150	es. 1295
Load weight / Greutate incarcatura	Kg	200	200	350	350
Load height / Inaltime incarcatura	mm	490 (420)*	490 (420)*	700 (620)*	800 (740)*
Tank capacity / Capacitate rezervor	lt	175	175	280	300
Spray rate / Rata pulverizare	l/min	170	2x110	2x160	2x200
Spray pressure / Preziune pulverizare	bar	2,3	2,5	2,4	2,3
Pump / Pompa	hp	2	2x1,2	2x2	2x2
Water heater / Incalzitor apa	kW	6	6	10	12
Power requirements / Cerinte alimentare (putere)	kW	7,5	7,8	13	15
Voltage / Voltaj	V	230/400	230/400	230/400	230/400
Phases / Faze	Ph	3	3	3	3
Timer / Temporizator	min	0 - 60	0 - 60	0 - 60	0 - 60
Cleaning temperature / Temperatura curatare	°C	0° - 60°	0° - 60°	0° - 60°	0° - 60°
Width / Latime	mm	1300	1300	1570	1970
Depth (lid open) / Adancime (cu capacul deschis)	mm	1350	1350	1830	2100
Height (lid open) / Inaltime (cu capacul deschis)	mm	2000	2000	2175	2425
Shipping dim. / Dimensiuni cu ambalaj	mm	1300x1060x1450	1300x1060x1450	1500x1650x1650	2000x1900x1700
Net weight / Greutate neta	Kg	190	200	335	480
Pneumatic lid / Capac pneumatic		-	-	-	<b>STANDARD</b>
Motorised basket / Rotatia motorizata a cosului		-	-	-	<b>STANDARD</b>


We reserve the right to modify without notice - Ne rezervam dreptul de a face modificari in brosură fara a anunta in prealabil

**OPTIONAL**


- Electro fan for steam outlet
- Ventilator electric pentru evacuarea aburului



- Removable basket with trolley
- Cos detasabil cu carucior



- Oil skimmer
- Skimmer ulei



- Motorized basket
- Invertirea motorizata a cosului

- Stainless steel water circuit and basket
- Circuit de apa si cos din otel inoxidabil

- Tank refilling
- Reumplere rezervor

- Drain pump
- Pompa de scurgere

- Insulation > 60 °C
- Izolatie > 60 °C